

RELTEC® CUADRADO TEXTURA

DESCRIPTION

SELF-SUPPORTING disposable formwork made up of **textured plastic materials**, a piece of **expanded polystyrene (EPS)** that gives it shape and an **external fiberglass reinforcement** to withstand the pressure of the concrete.

USE

- Formwork for reinforced concrete pillars, of square or rectangular section, with texturized and visible finish.

TECHNICAL CHARACTERISTICS

Characteristics	Value
Section	From 200x200 to 400x400 mm
Finish	Textured with sharp edges
Stripping	Cut at the mark. No stripping substances are required
Standard height	4000 mm
Maximum height of manufacture	4000 mm
Interior waterproofing	Resistant to concrete moisture
Tightness	COMPLETELY TIGHT for smooth and visible finishes



OUTSIDE DIAMETER (mm)

SECTION	150	200	250	300	350	400
150	250					
200	292	320				
250	338	361	390			
300	384	404	430	461		
350	432	449	472	500	531	
400	480	495	516	541	570	602

WEIGHT (Kg/m)

SECTION	150	200	250	300	350	400
150	1,59					
200	1,92	2,20				
250	2,37	2,56	2,87			
300	2,89	3,02	3,26	3,61		
350	3,49	3,58	3,78	4,03	4,63	
400	4,17	4,20	4,33	4,77	5,12	5,53



TEXTURE

MOD. 005

Wood texture

Important notes:

- In sections larger than 400x400, Reltec formworks may suffer minimal rounding deformities in the faces and corners at an approximate height of 1 metre, which are caused by the high pressure exerted by the concrete in this area. Similarly, for greater than standard heights, it is not possible to guarantee the precision of the chamfered or sharp edges or the flatness of its faces, especially in the lower part of the formwork.
- For protection, covering with plastic is recommended to prevent the formwork being exposed to sun or rain during storage. Similarly, avoid putting weight on the formwork so as not to cause deformities.